

## PRODUCT DATA SHEET

January, 2007

## McCLAIN INTERMODAL

### GENERAL INFORMATION

This container is not to be used for free liquid storage.

### WEIGHTS AND MEASURES

» Capacity:	20 yd <sup>3</sup> roll-tarp 25 yd <sup>3</sup> roll-tarp and metal lid 30 yd <sup>3</sup> roll-tarp and metal lid
» Height:	20 yd <sup>3</sup> : 5'-10½" 25 yd <sup>3</sup> : 7'-3" (to top of iso casting) 30 yd <sup>3</sup> : 8'-1" (to top of iso casting)
» Width :	All sizes: 8'-0"
» Length:	All sizes: 19'-10½"
» Weight:	20 yd <sup>3</sup> : RT – 6600 lbs. 25 yd <sup>3</sup> : RT – 7859 lbs., ML – 8059 lbs. 30 yd <sup>3</sup> : Contact Baker
» Inside Dimensions:	20 yd <sup>3</sup> : 82" wide x 222-7/8" long 25 yd <sup>3</sup> : 82" wide x 227-1/2" long 30 yd <sup>3</sup> : 82" wide x 227-1/2" long

### STRUCTURAL DESIGN

» Floor:	7-gauge steel
» Walls:	7-gauge steel
» Floor Frame:	3" channel
» Door/Header:	4" x 4" tubing outer frame with one 4" x 4" horizontal crossmember, 10-ga door
» Bulkhead:	4" x 6" corner posts with two 2" x 4" intermediate posts
» Corners:	Eight standard ISO corner castings
» Guide Rails:	2" x 6" tubing on 38" centers

### FEATURES

» Lid Options:	Roll-tarp, metal lid and aluminum lid
» Wheels:	Four wheels 10" diameter x 7½" wide
» Nose Rollers:	Two 6½" wide x 4" dia, bulkhead end
» Metal Lid Pull-Downs:	Three ratcheted chains on each side of container
» Pull Hook:	1¼" thick J-hook on 1" plate, bulkhead end
» Forklift Pockets:	None
» Gaskets:	Door- pure neoprene SCE44/45 Lid- ISOLOSS LS-1525 & LS-1550
» Door Locks:	One chain/ratchet each side of door plus three grab hands underneath
» Door Hinges:	Three top-mounted; door swings up.

### SURFACE DETAILS

» Exterior Coating:	High Gloss Polyurethane
» Interior Lining:	Polyliners only, no coating
» Placard Mounts:	Four

### TESTS/CERTIFICATIONS

» Tests Performed:	Water test after manufacture. Level I, II and III inspections thereafter.
» Certification:	AARM930-90, and some are CSC

